RIBAG

AROA with acrylic glass diffuser Pendant lamps



Product description

Art. No.: 4131.150.30.0 Product name: AROA pendant lamp Housing colour: natural anodised Material: Extruded aluminium Equipment: For mounting on the ceiling, 2 nickel-plated copper cables, transparently sheathed length 2500 mm, continuously adjustable height Dimensions (mm): 1500 x 28 x 32 Optics/light technology: acrylic glass diffuser opal Weight (kg): 1.72 Protection level: IP 20 Protection class: I Control gear: PS 230 V/50 Hz (in a separate housing) Lighting control: on/off


Light specification/technical data

Lamp: LED System power (W): 29 Light flux (lm/lamp): 3300 Luminous efficiency (lm/W): 114 Colour temperature (K): 3000 Colour rendering index (CRI): >90 Unified glare rating (UGR): 25 Light distribution: All-round beam Lifetime: 50'000h L90 B10 (Ta 25° C) Energy efficiency: D Colour consistency (MacAdam): 3

Specification text/Description: Article: 4131.150.30.0; Article name: AROA pendant lamp; Description: With perfect workmanship and sleek, classic design, the delicate lamp offers a particularly wide range of applications. The splash-proof mounted lamp with external control gear is also suitable for use in wet locations. A perforated metal diffuser that clips on is an optional accessory for perfect antiglare.; Color: natural anodised; Optics: acrylic glass diffuser opal; Light control: on/off; Watt: 29W; Kelvin: 3000K; Lumen: 3300lm/lamp; Materialisation: aluminium; Control gear: control gear 230 V/50 Hz; CRI: >90; Protection class: I; Protection level: IP 20; UGR: 25; Weight (incl. packaging): 1,72kg; Lenght: 1500mm; Dimension: 1500 x 28 x 32mm

Drawings


Art. No.: 4131.150.30.0



RIBAG Licht AG Kanalstrasse 18 5745 Safenwil / Schweiz

info@ribag.com www.ribag.com T +41 62 737 90 10 The technical data refer to rated values at an ambient temperature of 25°C and are guide values with a tolerance of +/- 10%. Subject to change without notice. No liability is accepted for printing errors. Prices are subject to change without notice. © RIBAG Lint AG 21.10.2023

Light distribution



Specifications

