



Clara

Designed by Piero Lissoni, 2015

57W - 3141lm - 2700K

eCeiling/wall lighting fixture, providing diffused light. The front diffuser is made of high efficiency, injection moulded opal Polycarbonate. Ceiling/wall fitting is in injection moulded polycarbonate. Dimmable Led light source powered without the use of any power supply/transformer, but directly by the mains voltage (220-230 V AC). For decorative purposes an optional accessory made of PC and ABS+PC is made available in 4 different finishes: chrome, copper, black fumée and transparent.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

| EAN | 8059607015322 |
|-------------------|--------------------------|
| Mounting | Ceiling and wall surface |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | LED Module |
| Power (W) | 57 |
| System flux (lm) | 3141 |

Physical

| Colour | White |
|---------------------|-------|
| Net weight (kg) | 3 |
| Package height (mm) | 110 |
| Package width (mm) | 670 |
| Package length (mm) | 680 |
| Package volume (m3) | 0.05 |
| IP internal | 40 |



Download

| Mounting instructions | 业 PDF |
|-----------------------|--------------|
| Compatible dimmers | ⊥ PDF |
| Spare Parts | .↓. PDF |

Photometric Files

LDT / IES



Technical Drawings

| 2D | 工 | ZIP |
|----|---------|-----|
| 3D | <u></u> | ZIP |









































https://professional.flos.com/en/global/product/clara-f1570009/

F1570009

Schematic light drawing



| Beam Angle: | | 117° |
|-------------|-------|-------|
| h(m) | E(lx) | D(m) |
| 1 | 969 | 3.28 |
| 2 | 242 | 6.56 |
| 3 | 108 | 9.83 |
| 4 | 61 | 13.11 |
| 5 | 39 | 16.39 |

Luminous flux luminaire 3141 lm

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**



Replaceable (LED only) light source by a professional

Photometric

| Light distribution | Roto symmetric |
|--------------------|----------------|
| CCT (K) | 2700 |
| Extreme cut off | No |


Electrical

| Insulation class | II |
|----------------------|---|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| LED voltage Vf (Vdc) | null |
| Power Supply | Integrated |
| Dimmable | Yes |
| Power Supply Type | Mains Cut Dimming |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |

Accessories & Power Supply



Spare Parts



01. Kit diffuser RF1570200

02. Kit of n.4 screws & hexagonal RF1570100 screwdriver

DOWNLOAD





RF1570200

Kit diffuser

RF1570100

Kit of n.4 screws & hexagonal screwdriver