




SUPERLOOP POWERBOX H9 900mA DIM5 B

20548 0015 B

AVAILABLE IN
BLACK 20548 0015 B
WHITE 20548 0015 W



 [View on website](#)

General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 900mA / 38W $\lambda > 0,9$ Inrush current : 5A - 50 μ s @ 230V-AC Max. 50 units on circuit breaker B 16A

Electrical info

CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI

For detailed installation instructions, please consult the manual: [20548_0015_HAND.pdf](#)

SUPERLOOP POWERBOX H9 900mA DIM5 B

20548 0015 B

WHERE USED

321 109 92	SUPERLOOP HC 90 SBL 927
321 109 93	SUPERLOOP HC 90 SBL 930
321 112 92	SUPERLOOP HC 120 SBL 927
321 112 93	SUPERLOOP HC 120 SBL 930
321 209 93	SUPERLOOP HC 90 SPR 930
321 212 93	SUPERLOOP HC 120 SPR 930
321 509 92	SUPERLOOP VC 90 SBL 927
321 509 93	SUPERLOOP VC 90 SBL 930
321 512 92	SUPERLOOP VC 120 SBL 927
321 512 93	SUPERLOOP VC 120 SBL 930
20562 9200	SUPERLOOP PLUS HC 90 SBL 927
20562 9300	SUPERLOOP PLUS HC 90 SBL 930
20563 9200	SUPERLOOP PLUS HC 120 SBL 927
20563 9300	SUPERLOOP PLUS HC 120 SBL 930
20570 9200	SUPERLOOP HC SBL OVAL S 927
20570 9300	SUPERLOOP HC SBL OVAL S 930
20571 9200	SUPERLOOP HC SBL OVAL M 927
20571 9300	SUPERLOOP HC SBL OVAL M 930
20573 9200	SUPERLOOP SLIM IN 90 SBL 927
20573 9300	SUPERLOOP SLIM IN 90 SBL 930
20574 9200	SUPERLOOP SLIM IN 120 SBL 927
20574 9300	SUPERLOOP SLIM IN 120 SBL 930
20577 9200	SUPERLOOP SLIM OUT 90 SBL 927
20577 9300	SUPERLOOP SLIM OUT 90 SBL 930
20578 9200	SUPERLOOP SLIM OUT 120 SBL 927
20578 9300	SUPERLOOP SLIM OUT 120 SBL 930
20582 9200	SUPERLOOP SLIM DOWN 120 SBL 927
20582 9300	SUPERLOOP SLIM DOWN 120 SBL 930

Notes: