



**luci control** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

**integrierter Bewegungsmelder**

**Erfassungswinkel 120°**  
Zeiteinstellung 5 Sek. – 8 Min.  
Dämmerungseinstellung 3-1000 Lux  
Reichweite 9 m

**Installation:**  
2x Kabeleinführung; Anschlussklemme 4x 2,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss pulverbeschichtet  
+ Glaslinse

**Schutzart: IP65**

**Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F**

**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

**integrated motion detector**

**detection angle 120°**  
time setting 5 sec. – 8 min.  
twilight setting 3-1000 lux  
range 9 m


**installation:**  
2x cable entry point; connection terminal 4x 2,5 mm<sup>2</sup>

**material:**  
aluminium die-casting powder-coated  
+ glass lens

**protection class: IP65**

**This product contains a light source of energy efficiency class F**

**light direction:**



**Farbe**  
colour

**Art.-Nr.**  
item no.

**Systemleistung**  
system performance



**anthracite**  
RAL 7016

93151-AN

**12 W/720 lm**



**deep black**  
RAL 9005

93151-BL

**12 W/720 lm**

**Größe in mm**  
size in mm