

FLOS

F011W30D055 Brushed Stainless Steel

Captain Flint Outdoor W1 Dimmable DALI


Designed by Michael Anastassiades, 2020



Luminaire for wall-mounting with diffuse light emission and fixed head. LED light source included. Integrated 220-240V ON/OFF or 1-10V/DALI dimmable electrical power. Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included. 110V version upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




Main specifications

| | |
|------------------|--------------------------|
| Mounting | Ceiling and wall surface |
| LED type | LED array |
| Lamp category | LED |
| Number of heads | 1 |
| Power (W) | 9.5 |
| Source flux (lm) | 1026 |
| System flux (lm) | 652 |

Physical

| | |
|---------------------|-------------------------|
| Colour | Brushed Stainless Steel |
| Trim | No |
| Orientation | Fixed |
| Recessed depth (mm) | 0 |
| Spot diameter (mm) | 208 |
| Length (mm) | 336 |
| Net weight (kg) | 2.1 |
| IP internal | 65 |

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric


| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 112 |
| Beam angle C90-270 (°) | 112 |

Electrical


| | |
|--------------------|-----------------|
| Insulation class | I |
| Frequency (Hz) | 50-60 |
| Main voltage (Vac) | 220-240 |
| Driver | Integrated |
| Dimmable | Yes |
| Dimming type | Dimmable DALI 1 |
| Precabled | no |
| Emergency type | No |
| Batteries inside | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

110V version upon request.