

## **GU10 600LM 5.7W 2700K DIMMABLE 36 BEAM INTEGRAL**

ILGU10DC117



The Integral LED High Lumen GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the High Lumen offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

#### **Details**

Quick Order Code: 765552

**Barcode:** 5055788255567

Category: Lamps

Range Name: 240V GU10 Base

Product Type: GU10
Product Body Finish: Matt white

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

## **Physical Data**

Product Length (mm): 54
Product Width (mm): 50
Product Weight (g): 27

Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded

diffuser

Base Term: GU10
Bulb Base: GU10

Construction: Plastic White and "Classic look" diffuser lens

Globe Finish: Clear Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Spot Type: SMD

#### **Electrical Data**

Power (W): 5.7 Power Consumption (W): 5.7 Power Factor: 0.5
Wattage equivalent (W): 75
Amperage (mA): 33

**Dimming:** Dimmable with compatible dimmers

Driver Included: Yes
Electric Current: AC
True Wattage Eq (W): 75

**EN:** EN-62560

LVD Certified: Yes

### **Light Data**

Luminous Flux in Lumens (Im): 600
Luminous efficacy (Im/W): 95
Peak Intensity (Cd): 1050
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:36Colour Rendering Index (CRI):80

Compatible Dimmers: Varilight JQP401W

Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


**LED Type:** Surface mounted device (SMD)


Lifetime (hours): 25000
Switching Cycles: 12500
Useful Lumens (lm): 540

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating: A**+ **New Energy Rating:** Е Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection): IP20 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





# **Packaging**

Package Weight (g): 36
Package Length (mm): 62
Package Width (mm): 48
Package Depth (mm): 48
Qty per euro pallet: 7200