

DISCOUNT LEVEL B

Model	Installation height(m)	Duration	Battery	Lumens	Light source	€
Non-maintained:						
Block N30	2 to 4	1 h	Ni-Cd	180	MHB _{LED}	-----

Block A Block TCA

Specifically for Self-test
Specifically for Self-test and DaisaTest System.

Includes microprocessor for Self-test mode operation **A** or DaisaTest centralised management system **TCA**
Fill out the reference with **A** or **TCA** depending on the model. TEV test control unit for Block TCA: See page 117
Example of order: Block P30 A / Block P30 TCA

Model	Installation height(m)	Duration	Battery	Lumens	Light source	A €	TCA €
Maintained: (1)							
				Emerg. Lum.			
Block P30 <input type="checkbox"/>	2 to 4	1 h	Ni-Mh	200	120	MHB _{LED}	-----
Block 2P30 <input type="checkbox"/>	2 to 4	2 h	Ni-Mh	200	120	MHB _{LED}	-----
Block 3P30 <input type="checkbox"/>	2 to 4	3 h	Ni-Mh	170	120	MHB _{LED}	-----

Block DALI | Specifically for DALI System

Models for the DALI system are available. By arrangement with the factory.

Block Luminaire | DOES NOT INCLUDE BATTERY Luminaire specific function

Model	Installation height(m)	Power supply	Lumens	Light source	€
Block L30	2 to 4	See power supply	200	LED	-----

Operation, shared data and notes:

The emergency luminaires equipped with Ni-Mh battery technology include a pulse-load microprocessing system that enables an important reduction of energy consumption.


The A and TCA Maintained models have an Eco-maintained function.

(1) Maintained models have a separate connection to the mains that enables turning the luminaire on/off at will.

Features plug & play and anchoring system.

Built to the EN 60598-2-22 (IEC 60598-2-22) standard. Protection rating: **IP43 IK04**.

Block Block



■ Finishes

DISCOUNT LEVEL B

Finish of	Description	Marking	Incr. €
Colour	White (as standard)	-----	-----
	Silver grey	(RAL9006)	-----
	Black	(N)	-----
LED colour	Cool white (as standard)	-----	-----
	Warm white. The luminous flux is reduced by 25% <i>Only Maintained and Luminaire models</i>	(WW)	-----
Power supply: Self-contained	220-230V 50/60Hz	-----	-----
	110-127V 50/60Hz	(110-127V)	-----
Luminaires	110-240V 50/60Hz, 170-320V DC	-----	-----
	24V 50/60Hz, 18-30V DC	(24V)	-----

■ Interdistance example

