

# Lens Ceiling-mounted

Emergency luminaires

DISCOUNT LEVEL B

Model	Installation height(m)	Duration	Format	Lumens	Light source	€
<b>Non-maintained:</b>						
Lens N20 (AD)	2.0 to 2.5	1h	Short	120	MHBLED	-----
Lens N30 (AD)	2.5 to 4.0	1h	Short	200	MHBLED	-----
Lens N40 (AD)	4.0 to 7.0	1h	Short	200	MHBLED	-----
Lens N70 (AD)	7.0 to 15.0	1h	Short	200	MHBLED	-----
Lens 2N20 (AD)	2.0 to 2.5	2h	Length	120	MHBLED	-----
Lens 2N30 (AD)	2.5 to 4.0	2h	Length	200	MHBLED	-----
Lens 2N40 (AD)	4.0 to 7.0	2h	Length	200	MHBLED	-----
Lens 2N70 (AD)	7.0 to 15.0	2h	Length	200	MHBLED	-----
Lens 3N20 (AD)	2.0 to 2.5	3h	Length	120	MHBLED	-----
Lens 3N30 (AD)	2.5 to 4.0	3h	Length	180	MHBLED	-----
Lens 3N40 (AD)	4.0 to 7.0	3h	Length	180	MHBLED	-----
Lens 3N70 (AD)	7.0 to 15.0	3h	Length	180	MHBLED	-----

Model	Installation height(m)	Duration	Format	Lumens	Light source	€
<b>Maintained: (1)</b>						
				<b>Emerg. Lum.</b>		
Lens P20 (AD)	2.0 to 2.5	1h	Short	120 70	MHBLED	-----
Lens P30 (AD)	2.5 to 4.0	1h	Short	200 110	MHBLED	-----
Lens P40 (AD)	4.0 to 7.0	1h	Short	200 110	MHBLED	-----
Lens P70 (AD)	7.0 to 15.0	1h	Short	200 110	MHBLED	-----
Lens 2P20 (AD)	2.0 to 2.5	2h	Length	120 70	MHBLED	-----
Lens 2P30 (AD)	2.5 to 4.0	2h	Length	200 110	MHBLED	-----
Lens 2P40 (AD)	4.0 to 7.0	2h	Length	200 110	MHBLED	-----
Lens 2P70 (AD)	7.0 to 15.0	2h	Length	200 110	MHBLED	-----
Lens 3P20 (AD)	2.0 to 2.5	3h	Length	120 70	MHBLED	-----
Lens 3P30 (AD)	2.5 to 4.0	3h	Length	180 110	MHBLED	-----
Lens 3P40 (AD)	4.0 to 7.0	3h	Length	180 110	MHBLED	-----
Lens 3P70 (AD)	7.0 to 15.0	3h	Length	180 110	MHBLED	-----

## Lens Ceiling-mounted A Lens Ceiling-mounted TCA

Specifically for Self-test

Specifically for Self-test and DaisaTest System.

Includes microprocessor for Self-test mode operation **A** or DaisaTest centralised management system **TCA**  
Fill out the reference with **A** or **TCA** depending on the model. TEV test control unit for Lens (AD) TCA: See page 117  
Example of order: Lens N20 A (AD) / Lens N20 TCA (AD)

Model	Installation height(m)	Duration	Format	Lumens	Light source	A €	TCA €
<b>Non-maintained:</b>							
Lens N20 <input type="checkbox"/> (AD)	2.0 to 2.5	1h	Short	120	MHBLED	-----	-----
Lens N30 <input type="checkbox"/> (AD)	2.5 to 4.0	1h	Short	200	MHBLED	-----	-----
Lens N40 <input type="checkbox"/> (AD)	4.0 to 7.0	1h	Short	200	MHBLED	-----	-----
Lens N70 <input type="checkbox"/> (AD)	7.0 to 15.0	1h	Short	200	MHBLED	-----	-----
Lens 2N20 <input type="checkbox"/> (AD)	2.0 to 2.5	2h	Length	120	MHBLED	-----	-----
Lens 2N30 <input type="checkbox"/> (AD)	2.5 to 4.0	2h	Length	200	MHBLED	-----	-----
Lens 2N40 <input type="checkbox"/> (AD)	4.0 to 7.0	2h	Length	200	MHBLED	-----	-----
Lens 2N70 <input type="checkbox"/> (AD)	7.0 to 15.0	2h	Length	200	MHBLED	-----	-----
Lens 3N20 <input type="checkbox"/> (AD)	2.0 to 2.5	3h	Length	120	MHBLED	-----	-----
Lens 3N30 <input type="checkbox"/> (AD)	2.5 to 4.0	3h	Length	180	MHBLED	-----	-----
Lens 3N40 <input type="checkbox"/> (AD)	4.0 to 7.0	3h	Length	180	MHBLED	-----	-----
Lens 3N70 <input type="checkbox"/> (AD)	7.0 to 15.0	3h	Length	180	MHBLED	-----	-----

Model	Installation height(m)	Duration	Format	Lumens	Light source	A €	TCA €
<b>Maintained: (1)</b>							
				<b>Emerg. Lum.</b>			
Lens P20 <input type="checkbox"/> (AD)	2.0 to 2.5	1h	Short	120 70	MHBLED	-----	-----
Lens P30 <input type="checkbox"/> (AD)	2.5 to 4.0	1h	Short	200 110	MHBLED	-----	-----
Lens P40 <input type="checkbox"/> (AD)	4.0 to 7.0	1h	Short	200 110	MHBLED	-----	-----
Lens P70 <input type="checkbox"/> (AD)	7.0 to 15.0	1h	Short	200 110	MHBLED	-----	-----
Lens 2P20 <input type="checkbox"/> (AD)	2.0 to 2.5	2h	Length	120 70	MHBLED	-----	-----
Lens 2P30 <input type="checkbox"/> (AD)	2.5 to 4.0	2h	Length	200 110	MHBLED	-----	-----
Lens 2P40 <input type="checkbox"/> (AD)	4.0 to 7.0	2h	Length	200 110	MHBLED	-----	-----
Lens 2P70 <input type="checkbox"/> (AD)	7.0 to 15.0	2h	Length	200 110	MHBLED	-----	-----
Lens 3P20 <input type="checkbox"/> (AD)	2.0 to 2.5	3h	Length	120 70	MHBLED	-----	-----
Lens 3P30 <input type="checkbox"/> (AD)	2.5 to 4.0	3h	Length	180 110	MHBLED	-----	-----
Lens 3P40 <input type="checkbox"/> (AD)	4.0 to 7.0	3h	Length	180 110	MHBLED	-----	-----
Lens 3P70 <input type="checkbox"/> (AD)	7.0 to 15.0	3h	Length	180 110	MHBLED	-----	-----

## Lens Ceiling-mounted DALI | Specifically for DALI System

Models for the DALI system are available. By arrangement with the factory.


## Lens Ceiling-mounted Luminaire

**DOES NOT INCLUDE BATTERY**  
Luminaire specific function


Model	Installation height(m)	Format	Lumens	Light source	€
Lens L20 (AD)	2.0 to 2.5	Short	120	MHBLED	-----
Lens L30 (AD)	2.5 to 4.0	Short	200	MHBLED	-----
Lens L40 (AD)	4.0 to 7.0	Short	200	MHBLED	-----
Lens L70 (AD)	7.0 to 15.0	Short	200	MHBLED	-----

## Lens Ceiling-mounted Lens (AD)

Short format



Long format



■ Finishes

DISCOUNT LEVEL B

Finish of	Description	Marking	Incr. €
Colour	White (as standard)	-----	-----
	Silver grey	(RAL9006)	-----
	Black	(N)	-----
LED colour	Cool white (as standard)	-----	-----
	Warm white. The luminous flux is reduced by 20% <i>Only Maintained and Luminaire models</i>	(WW)	-----
Power supply: Self-contained	220-230V 50/60Hz	-----	-----
	110-127V 50/60Hz	(110-127V)	-----
Luminaires	110-240V 50/60Hz, 170-320V DC	-----	-----
	24V 50/60Hz, 18-30V DC	(24V)	-----



**Operation, shared data and notes:**

The emergency luminaires equipped with Ni-Mh battery technology include a pulse-load microprocessing system that enables an important reduction of energy consumption.

The A and TCA Maintained models have an Eco-maintained function.

(1) Maintained models have a separate connection to the mains that enables turning the luminaire on/off at will.

Features plug & play and anchoring system.

Built to the EN 60598-2-22 (IEC 60598-2-22) standard. Protection rating: IP40 IK04.