


MIRAGE W


Design: Nital Patel



*Anodized surfaces are not recommended for outdoor use.
Anodized surfaces may vary $\pm 10\%$.



MIRAGE W1



MIRAGE W2

MIRAGE W - 2700/3000K

Design: Nital Patel

LIGHT·POINT
C O P E N H A G E N

| ART. NAME | MIRAGE W1 | MIRAGE W2 | |
|-------------------------|-------------------|-------------------|---|
| Art. no. white | 271041 | - | - |
| Art. no. black | 271040 | 271050 | - |
| Art. no. rose gold | 271043 | - | - |
| Art. no. titanium | 271044 | - | - |
| Art. no. brass | 271045 | - | - |
| Art. no. rust | 271042 | 271052 | - |
| EAN white | 5711389710415 | - | - |
| EAN black | 5711389710408 | 5711389710507 | - |
| EAN rose gold | 5711389710439 | - | - |
| EAN titanium | 5711389710446 | - | - |
| EAN brass | 5711389710453 | - | - |
| EAN rust | 5711389710422 | 5711389710521 | - |
| Material | Aluminium / Glass | Aluminium / Glass | - |
| Light source | LED | LED | - |
| Lifetime | 50.000 | 50.000 | - |
| Number of light sources | 2 | 2 | - |
| Electronical gear | N/A | N/A | - |
| Driver watt | N/A | N/A | - |
| Light source watt | 4.5 | 7 | - |
| System watt | 9 | 14 | - |
| Voltage | 220-240 | 220-240 | - |
| Dimmable | Yes | Yes | - |
| Lumen output | 675 (nominal) | 1050 (nominal) | - |
| Lumen pr. watt | 75 | 75 | - |
| Flux | N/A | N/A | - |
| CCT (K) | 2700/3000 | 2700/3000 | - |
| RA/CRI | 90 | 90 | - |
| Mac Adam | 5 | 5 | - |
| Light distribution | Up/Down | Up/Down | - |
| Beam angle | 90 | 90 | - |
| Tilt angle | N/A | N/A | - |
| Cutout mm. | N/A | N/A | - |
| Rotation | N/A | N/A | - |
| Looping | N/A | N/A | - |