



Heavy Metal Wall 2 Mono NEW

Designed by FLOS Outdoor



LED source included. Electric remote 24V dc ON/OFF power supply to be ordered separately. Wall fixing bracket included. The luminaire is equipped with a protruding, neoprene, 250 mm cable and a wiring kit with crimp connectors and adhesive heatshrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	vvali
Environments	Outdoor wet location
LED type	Power LED
Number of heads	1
Power (W)	2.2
System power (W)	3.4
Source flux (lm)	199
System flux (lm)	121

Physical

Colour	Anthracite	
Orientation	Fixed	
IP internal	65	

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	₹ ZIP
3D	₺ ZIP











Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Non-replaceable light source

https://professional.flos.com/en/global/product/heavy-metal-wall-2-mono-fa50701533/

FA50701533

Schematic light drawing



Beam Angle:		23°
h(m)	E(lx)	D(m)
1	520	0.41
2	130	0.82
3	58	1.23
4	32	1.64
5	21	2.05

Luminous flux luminaire 121 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	24
Beam angle C90-270 (°)	24

Electrical

Insulation class	III
Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Power supply

RF25754

'Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP20 Class II selv._Non Dimmable



OPTIONAL Power supply

RF25757

Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable



OPTIONAL Power supply

RF25752

Power supply 24Vdc 20W / 220-240V IP67 Class II selv. Non Dimmable



OPTIONAL Power supply

RF25747

Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL Power supply

RF25748

Power supply dual function Vout 24Vdc: 8W/100÷240V lout 350ma: 6x1W/100÷240V IP65 Class II selv. Non Dimmable



OPTIONAL Power supply

F990B23A700

Power supply 24Vdc 35W /120-270V IP67 Class II selv.



OPTIONAL Power supply

E990R27A000

Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL Power supply

E990R28A000

Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable