Nowodvorski	
LIGHTING	

## CATALOGUE CARD

LIGHT SOURCE GU10 LIGHT SOURCES TYPE Replaceable MAXIMUM WATTAGE 10W only LED AMP INCLUDES SOURCE OF LIGHT NO NUMBER OF LIGHT SOURCES 1 P IP20 Interior use CACKAGE DIMENSIONS 40.5cm/15.8cm L/W/H) NET/GROSS WEIGHT 0.705kg/1.055kg ASSEMBLY METHOD Bridge + conductor with plug LEADING/SUPPLEMENTARY COLOR Black,Brass SWITCH Yes MATERIALS Plywood,Braided cable,Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I MENSIONS LECTRICAL SECURITY CLASS I MENSIONS	UMINAIRE MODEL DOVE		-
LIGHT SOURCES TYPE Replaceable   MAXIMUM WATTAGE 10W only LED   AMP INCLUDES SOURCE OF LIGHT No   NUMBER OF LIGHT SOURCES 1   p IP   Interior use IP   ACKAGE DIMENSIONS 40.5cm/15.6cm/15.8cm   LW/H) Bridge + conductor with plug   LECTRICAL SECURITY CLASS I   SYTE Scandinavia   SYTE Scandinavia   SOWER SUPPLY ~220-230V/50/60Hz	926	4 COUNTRY OF ORIGIN	MADE IN POLANE
AAXIMUM WATTAGE AMP INCLUDES SOURCE OF LIGHT NO NUMBER OF LIGHT SOURCES 1 P IP IP20 Interior use INTERIOR EVEN EVEN EVEN EVEN ACKAGE DIMENSIONS 40.5cm/15.6cm/15.8cm LW/H) NET/GROSS WEIGHT 0.705kg/1.055kg ASSEMBLY METHOD Bridge + conductor with plug EADING/SUPPLEMENTARY COLOR Black,Brass SWITCH Yes Scandinavian ELECTRICAL SECURITY CLASS 5 9 0 3 1 3 9 9 2 6 4 9 2 MATERIALS 5 9 0 3 1 3 9 9 2 6 4 9 2	LIGHT SOURCE GU	10	
AMP INCLUDES SOURCE OF LIGHT No NUMBER OF LIGHT SOURCES 1 P IP20 Interior use INTERION INTERIOR INTERI	LIGHT SOURCES TYPE Replaceab	le	
NUMBER OF LIGHT SOURCES 1   p IP20   Interior use   ENECCEVES ()   ()   ()   ACKAGE DIMENSIONS   A0.5cm/15.6cm/15.8cm   ()   NUMH   NET/GROSS WEIGHT   0.705kg/1.055kg   ASSEMBLY METHOD   Bridge + conductor with plug   LEADING/SUPPLEMENTARY COLOR   Black,Brass   SWITCH   Y   Cover SUPPLY   -220-230V/50/60Hz   Support Clight Support	MAXIMUM WATTAGE 10W only LE	D	
P IP20 Interior use EXECCESE E E E E E E E E E E E E E E E E E	AMP INCLUDES SOURCE OF LIGHT	lo	
Interior use EXECCES S A S C S S S S S S S S S S S S S S S	NUMBER OF LIGHT SOURCES	1	
EICCEUE E A O CONTRACTOR A O SECONDA S	P IP2	20	
ACKAGE DIMENSIONS 40.5cm/15.6cm/15.8cm L/W/H) NET/GROSS WEIGHT 0.705kg/1.055kg ASSEMBLY METHOD Bridge + conductor with plug LEADING/SUPPLEMENTARY COLOR Black,Brass SWITCH Yes MATERIALS Plywood,Braided cable,Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I DOWER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	Interior us	se 🗾	
L/W/H) NET/GROSS WEIGHT 0.705kg/1.055kg ASSEMBLY METHOD Bridge + conductor with plug LEADING/SUPPLEMENTARY COLOR Black,Brass SWITCH Yes MATERIALS Plywood,Braided cable,Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I POWER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2			
ASSEMBLY METHOD Bridge + conductor with plug LEADING/SUPPLEMENTARY COLOR Black, Brass SWITCH Yes MATERIALS Plywood, Braided cable, Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I POWER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	PACKAGE DIMENSIONS <b>40.5cm/15.6cm/15.8c</b> [L/W/H]	m	
LEADING/SUPPLEMENTARY COLOR Black, Brass SWITCH Yes MATERIALS Plywood, Braided cable, Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I POWER SUPPLY ~220-230V/50/60Hz 5903139926492	NET/GROSS WEIGHT 0.705kg/1.055kg	(g	
SWITCH Yes MATERIALS Plywood, Braided cable, Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I POWER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	ASSEMBLY METHOD Bridge + conductor with plu	ıg	
MATERIALS Plywood, Braided cable, Painted steel STYLE Scandinavian ELECTRICAL SECURITY CLASS I POWER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	LEADING/SUPPLEMENTARY COLOR Black,Bras	ss	
Style Scandinavian   DIMENSIONS DIMENSIONS OWER SUPPLY -220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	SWITCH Ye	25	
ELECTRICAL SECURITY CLASS     I       power SUPPLY     ~220-230V/50/60Hz       Image: Supply image: Suppl	MATERIALS Plywood,Braided cable,Painted ste		
POWER SUPPLY     ~220-230V/50/60Hz       Image: supply image: supp	STYLE Scandinavia	an DIMENSIONS	
2000 ER SUPPLY ~220-230V/50/60Hz 5 9 0 3 1 3 9 9 2 6 4 9 2	ELECTRICAL SECURITY CLASS	Y  ∢>	
5903139926492	POWER SUPPLY ~220-230V/50/60F	Hz T	X+Y+Z+A=max 500 cm
5903139926492		—	
×			
×			Â
×		E B	
5903139926492		×	0
H-SCORE	5 9 0 3 1 3 9 9 2 6 4 9 2		
H=50m		4	, ,
under Frank			
		e t	Ş
		→ B=50c	<u>ر</u>
		L	