

# FLOS

60.9276

**Continuous current power supply of 20-40W, DALI 2 110/240V - 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800 / 850 / 900 / 950 / 1000 / 1050 / 1200 mA...**



Continuous current power supply of 20-40W, 110/240V - 50/60Hz with power current selected through adjustable 350 mA - 18,5W / 400 mA - 21W / 500 mA - 26,5W / 600 mA - 31,5W / 650 mA - 34,5W / 700 mA - 37W / 750 mA - 39,5W / 800 / 850 / 900 / 950 / 1000 / 1050 / 1200 mA - 40W switch. Dali 2, 0/1-10V or push dimming, synchronisation cables not included, use 60.1665.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

## Main specifications

Ilcos No

## Physical

Trim No



GWT  
850°

## Electrical

Dimming type Dimmable DALI 2

Emergency type No

<https://professional.flos.com/en/global/product/continuous-current-power-supply-of-20-40w-dali-2-110-240v-50-60hz.-power-current-selected-through-adjustable-350ma-18-5w-400ma-21w-500ma-26-5w-600ma-31-5w-650ma-34-5w-700ma-37w-750ma-39-5w-800-850-900-950-1000-1050-1200-ma-...-60.9276/>

60.9276