| Nowodvorski |
|-------------|
| LIGHTING    |

## **CATALOGUE CARD**

| LUMINAIRE MODEL   | PAN LED S              | CATALOGUE GROUP   | -              |
|---|------------------------|-------------------|----------------|
|   | 8173                   | COUNTRY OF ORIGIN | MADE IN P.R.C. |
| LIGHT SOURCE  | LED                    |                   |                |
| LIGHT SOURCES TYPE                                      | Integrated             |                   |                |
| MAXIMUM WATTAGE   | 12W                    |                   |                |
| LAMP INCLUDES SOURCE OF LIGHT                           | Yes                    |                   |                |
| IP  | IP44                   |                   |                |
|   | Interior use           |                   |                |
| LIFETIME  | 20000h                 |                   |                |
| THIS PRODUCT 8173 CONTAINS 7906 OF ENERGY EFFICIENCY CL | ASS: F                 |                   |                |
|   | cm/34.5cm/14.5cm       |                   |                |
| NET/GROSS WEIGHT  | 2.59kg/2.9kg           |                   |                |
| ASSEMBLY METHOD   | Direct assembly        | DIMENSIONS        |                |
| LEADING/SUPPLEMENTARY COLOR                             | Transparent,C<br>hrome |                   |                |
| MATERIALS Glass,Ch                                      | rome plated steel      |                   |                |
| STYLE   | Modern                 |                   | 82 cm          |
|   | I                      |                   | 8              |
| ELECTRICAL SECURITY CLASS                               |                        |                   |                |



| Item No. | POWER | COLOR TEMP | LUMEN | BEAM ANGLE | CRI | IP   | LED BRAND | DRIVER BRAND | LIFETIME | WARRANTY |  |
|----------|-------|------------|-------|------------|-----|------|-----------|--------------|----------|----------|--|
| 8173     | 12W   | 4000K      | 770lm | 120°       | ≥80 | IP44 | _         | _            | 20000h   | —        |  |

30 cm

-