



F011W40D030 Black

Captain Flint Outdoor W1 Dimmable DALI


Designed by Michael Anastassiades, 2020



Luminaire for wall-mounting with diffuse light emission and fixed head. LED light source included. Integrated 220-240V ON/OFF or 1-10V/DALI dimmable electrical power. Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included. 110V version upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling and wall surface
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	9.5
Source flux (lm)	1099
System flux (lm)	699

Physical

Colour	BIACK
Trim	No
Orientation	Fixed
Recessed depth (mm)	0
Spot diameter (mm)	208
Length (mm)	336
Net weight (kg)	2.1
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	₹ ZIP
3D	⊥ ZIP
a Bim	⊥ ZIP









IP 65

https://professional.flos.com/en/global/product/captain-flint-outdoor-w1-dimmable-dali-f011w40d030/

F011W40D030

Schematic light drawing



Beam Angle:		114°
h(m)	E(lx)	D(m)
1	242	3.05
2	60	6.11
3	27	9.16
4	15	12.22
5	10	15.27

0° 7 242 cd 7 30°	5	
uminous flux l uminaire		
99 lm		

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable DALI 1
Precabled	no
Emergency type	No
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	112
Beam angle C90-270 (°)	112

Notes

110V version upon request.