

# Impulse Round Wall 1x IP44 LED DE

137706XX\_137707XX

**1**

LED +  
LED -

SCREWS NOT INCLUDED  
max Ø4,5 mm

11mm  
0,2 - 4mm<sup>2</sup>  
24 - 12 AWG

**2**

**3**

T10

**4**

**LIGHT OUTPUT**

**INSTALL ABOVE EYE LEVEL**

**CAN BE USED WITH ELECTRICAL INSTALLATION BOX**

Ø145mm  
85mm  
30mm  
90mm  
Ø60mm

**IP44 - DEGREE OF PROTECTION**

IP44 only when used with included connectors

**ELECTRICAL SPECS LED-FIXTURE**

Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	10,8	12	3,8
500	10,8	12	5,5

**+** RED      **-** BLACK

For serial connection, respect polarity!  
Not suited for connection to mains voltage.  
Combine with a Modular LED-driver.

**LIGHT SOURCE - DO NOT TOUCH LED**

Touching the LED can result in permanent damage of the light source. The light source and/or driver contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

**PREVENTING ELECTROSTATIC DAMAGE**

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

**ACCESSORIES**

For available accessories check [www.supermodular.com](http://www.supermodular.com) or connect with your sales contact.