



1.0 LED

LED COB 12W | dimmable
220-240VAC | 50-60Hz | incl. driver
aluminium

IP20 0°-25°|355° 34° SDCM2 L80|50K 0.65kg

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-25°|355° 0.61kg

phase-cut dim

	CODE
	133764W_
	133764J_
	133764H_
	133764K_
	133764CH_
	133764P_
	133764Q_
	133764B_

DALI-2 | push dim

	CODE
	133765W_
	133765J_
	133765H_
	133765K_
	133765CH_
	133765P_
	133765Q_
	133765B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	745 >90	3
3000K	800 >90	5
2000-3000K	560 >90	9

	CODE
	133120W0
	133120J0
	133120H0
	133120K0
	133120CH0
	133120P0
	133120Q0
	133120B0

OPTIONAL

PAR16 6.5W GU10 phase-cut dim		CODE
	2700K 460lm	901228W3
	2700K 437lm	901228B3
	3000K 500lm	901228W5
	3000K 457lm	901228B5



MORE BEAM ANGLES ONLINE

weverducre.com/more-solid

SOLID

Ceiling surface

