







PLANO

Ceiling recessed



1.0 LED

LED COB 6/9W | 350/500mA | 17V aluminium

IP20 0°-35°|355° A 34° SDCM2 L80|55K 0.26kg

wire springs 74x78 95 2-18

CODE
118561W_
118561S_
118561Q_
118561B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	510/685	>90	3
3000K	550/740	>90	5
2000-3000K	365/535	>90	9

LED module 20 years replaceability

ALWAYS USE

driver | 500mA

	CODE
10W	90214406
10W dim	90224403
24W DALI	90244701

more options and specs on page 808

2.0 LED

2x COB 6/9W | 350/500mA | 17V aluminium

IP20 0°-35°|355° A 34° SDCM2 L80|55K 0.48kg

wire springs 74x148 95 2-18

CODE
118661W_
118661S_
118661Q_
118661B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x510/685	>90	3
3000K	2x550/740	>90	5
2000-3000K	2x365/535	>90	9

LED module 20 years replaceability

ALWAYS USE

driver | 500mA | only 1x needed

	CODE
20W	90218601
20W dim	90224602
24W DALI	90244701

more options and specs on page 807

1.0 PAR16

PAR16 max. 12W | GU10 100-240VAC | 50-60Hz aluminium

IP20 0°-35°|355° 0.24kg

wire springs 74x78 125 2-18

CODE
118120W0
118120S0
118120Q0
118120B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	460lm	>90	3
2700K	437lm	>90	5
3000K	500lm	>90	9
3000K	457lm	>90	5

LED module 20 years replaceability

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5

2.0 PAR16

2x PAR16 max. 12W | GU10 100-240VAC | 50-60Hz aluminium

IP20 0°-35°|355° 0.44kg

wire springs 74x148 125 2-18

CODE
118220W0
118220S0
118220Q0
118220B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	4x460lm	>90	3
2700K	4x437lm	>90	5
3000K	5x500lm	>90	9
3000K	4x457lm	>90	5

LED module 20 years replaceability

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5