

# NOVA LUCE

**Supplier's name or trade mark:** NOVA LUCE S.A  
**Supplier's address:** SCHIMATARI VIOTIAS 32009, GREECE  
**Model identifier:** 9053202  
**Type of light source:** LED



## Product information Sheet

### General Information

Material number	9053202
Type	Bathroom light
Product segment	INDOOR

### Dimensions

Length (in cm)	62 Cm
Width (in cm)	14 Cm
Height (in cm)	6 Cm
Net Weight	0.92 Kg

### Material & Colour

Enclosure Material	Aluminium & Acrylic
Colour	Sandy black
Adjustable	

### Functionality

Switch Type
Function
Battery
USB Charger

### Technical Information


Protection Degree	IP44
Protection Class	I
Mains Voltage	220-240V
max. Wattage	20W
Lumen	1615
Equivalence With Incandescent Lamp (W)	
Colour Temperature	3000K
Nominal Lifetime (in h)	50000H
Switching Cycles	-
Colour Rendering Index (Ra, CRI)	>80
Rated Lamp Power (0,1W precision)	
Colour Tolerance (LED, SDCM)	5,4

## Product information

Lighting technology used [LED/OLED/MIXED/OTHER]	LED
Non-directional or directional [NDLS/DLS]	NDLS
Mains or non-mains [MLS/NMLS]	NMLS
Connected light source (CLS) [yes/no]	No
Colour-tuneable light source [yes/no]	No
Envelope [no/second/non-clear]	No
High luminance light source [yes/no]	No
Anti-glare shield [yes/no]	No
Dimmable [yes/only with specific dimmers/no]	No

## General Product parameters

Energy consumption in on-mode (kWh/1000h)	20k
Energy efficiency class	F
The calculations performed with the parameters, including the determination of the energy class	F
Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1615lm
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set :	3079K
On-mode power ( $P_{on}$ ), expressed in W [x,x]	20.8w
Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	
Colour rendering index, rounded to the nearest integer , or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	
Spectral power distribution in the range 250 nm to 800 nm, at full-load	



$x=0.4280, y=0.397$

Chromaticity coordinates (x and y)

## Parameters for directional light sources

Peak luminous intensity (cd)	
Beam angle in degrees, or the range of beam angles that can be set	
Beam Angle in degrees for directional light source	

## Parameters for LED and OLED light sources

R9 colour rendering index value	2
Survival factor [x,xx]	1
The lumen maintenance factor [x,xx]	96%
Displacement factor ( $\cos \phi_1$ )	0,85
Colour consistency in McAdam ellipses	5
Displacement factor ( $\cos \phi_1$ ) for LED and OLED mains light sources	0,85
Colour consistency in MacAdam ellipse steps for LED and OLED light sources	5
Flicker metric (Pst Lm) [x,x]	0,019
Flicker metric (PstLM) for LED and OLED light sources	0,019
Stroboscopic effect metric (SVM) for LED and OLED light sources	0,003
Stroboscopic effect metric (SVM) [X,X]	0,003
$P_{on}$ in W	20.8w

