



DEEP point

Ceiling recessed

new



1.0

LED COB 4W | 250mA | 18V
aluminium

IP20 A 32° SDCM2 L80|50K 0.06kg

wire springs 40-41 68 4-25

| | CODE |
|--|----------|
| | 185261W_ |
| | 185261M_ |
| | 185261Q_ |
| | 185261B_ |

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K | 390 >90 | 3 |
| 3000K | 430 >90 | 5 |

ALWAYS USE

driver | 250mA

| | CODE |
|-----------|----------|
| 5W dim | 90226201 |
| 13W DALI* | 90246501 |

*revision opening required
more options and specs on page 806

1.0 IP44

LED COB 4W | 250mA | 18V
aluminium

IP44 A 32° SDCM2 L80|50K 0.06kg

wire springs 40-41 68 4-25

| | CODE |
|--|----------|
| | 185161W_ |
| | 185161B_ |

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K | 370 >90 | 3 |
| 3000K | 410 >90 | 5 |

ALWAYS USE

driver | 250mA

| | CODE |
|------------------|----------|
| 5W dim IP20 | 90226201 |
| 13W DALI IP20* | 90246501 |

*revision opening required
more options and specs on page 806