

FLOS

FA11727914733 Anthracite

Emma Wall 3 Mono NEW


Designed by FLOS Outdoor



LED source included. Electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 8mm<math>\leq \varnothing < 12\text{mm}</math> and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall
Environments	Outdoor wet location
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	12
System power (W)	14.5
Source flux (lm)	1895
System flux (lm)	1526

Physical

Colour	Anthracite
Orientation	Fixed
IP internal	66

Download

[Mounting instructions](#)  ZIP


Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



h(m)	E(lx)	D(m)
1	2990	0.68
2	747	1.36
3	332	2.04
4	187	2.71
5	120	3.39

Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	38
Beam angle C90-270 (°)	38

Electrical


Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	110-240
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles
IP68. ($\varnothing 7 \div 12$ mm cable).