

FLOS

FA11828215333 Anthracite

Emma Wall 4 Double NEW


Designed by FLOS Outdoor



LED source included. Electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 8mm$\leq \varnothing \leq 12\text{mm}$ and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall
Environments	Outdoor wet location
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	34
System power (W)	39
Source flux (lm)	2X2744
System flux (lm)	2X2030

Physical

Colour	Anthracite
Orientation	Fixed
IP internal	66

Download

[Mounting instructions](#) ZIP


Photometric Files

[LDT / IES](#) ZIP


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	40
Beam angle C90-270 (°)	40
Beam angle indirect C0-180 (°)	40
Beam angle indirect C90-270 (°)	40

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles
IP68. ($\varnothing 7 \div 12$ mm cable).