



FA11828215133 Anthracite

Emma Wall 4 Mono

NEW


Designed by FLOS Outdoor



LED source included. Electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 8mm<ø<12mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall
Environments	Outdoor wet location
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	17
System power (W)	20
Source flux (lm)	2744
System flux (lm)	2030

Physical

Colour	Anthracite
Orientation	Fixed
IP internal	66

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	<u>↓</u> ZI	Ρ
3D	↓ ZI	P









Schematic light drawing



Bean	n Angle:	41°
h(m)	E(lx)	D(m)
1	3825	0.74
2	956	1.49
3	425	2.23
4	239	2.98
5	153	3 72

Luminous flux luminaire 2030 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	40
Beam angle C90-270 (°)	40

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Dimmable	No
Dimmable Dimming type	No Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **D**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles IP68. (ø7÷12mm cable).