



FA53104333 Anthracite

Emma Ceiling 2 NEW



Designed by FLOS Outdoor



LED source included. Integrated electrical power supply 220-240V ON/OFF. With IP65 cable guide for rubber cables 5mm<ø<9mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling
Environments	Outdoor wet location
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	4.4
System power (W)	6
Source flux (lm)	510
System flux (lm)	363

Physical

Colour	Anthracite	
Orientation	Fixed	
IP internal	65	

Download

Mounting instructions

₹ ZIP

Photometric Files

LDT / IES

₩ ZIP

Technical Drawings

2D	$\overline{\gamma}$	ZIP
3D	$\overline{\mathbf{A}}$	ZIP









Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	329	1.24
2	82	2.49
3	37	3.73
4	21	4.97
5	13	6.22

Direct

4000

80

65

Symmetric

Luminous flux luminaire

Photometric

Beam angle C0-180 (°)

Lighting type

Electrical

Insulation class	II	
Frequency (Hz)	50-60	
Main voltage (Vac)	220-240	
Dimmable	No	
Dimming type	Non Dimmable	
Emergency type	No	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **D**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Beam angle C90-270

CCT (K)

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles IP68. (ø7÷12mm cable).