



WEVER & DUCRÉ
LIGHTING

DOCUS 1.0 LED

186359B5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Surface

Black Matt

RAL 9005^a

IP20

Interior

Output: 700 lm

CIE flux code: 96 100 100 100 100

LED

3000 K

CRI ≥ 90

3 SDCM

OPTICAL

Medium , Beam angle 21°

ELECTRICAL

DALI

220 - 240 V

Total connected power 8.0 W

Class 1

PHYSICAL

Length 90 mm

Width 90 mm


Height 90 mm

0.63 kg

^a Color may deviate slightly due to production conditions.



Squared ceiling surface mounted downlight made from die-cast aluminium; rounded edges; surface Black Matt; powder coated; matt texture; RAL 9005; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP20; PC1; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; optional single inner cover available; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

DOCUS 1.0 LED

186359B5

OPTICAL

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
DOCUS max. 10W	Black	62 · 62 · 39.5	9 1 1 0 2 1 B 1
DOCUS max. 10W	Gold	62 · 62 · 39.5	9 1 1 0 2 1 G 1
DOCUS max. 10W	White	62 · 62 · 39.5	9 1 1 0 2 1 W 1