

# OL 33

catalogue 2020 p. 132

ref. 144214014

EAN. 3663660280020

Model 6

## Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	1050mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened glass
Bulb cover	No
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	2446 lm
Total consumption	56 W
Standby power	-
Energy class	D (Source LED)
Luminous efficacy	43.7
IRC	80
SDCM	-
Optic	Yes
Dimmable	No
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	18%
Photobiological Risk group	-
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



# OL 33

catalogue 2020 p. 132

ref. 144214014

EAN. 3663660280020

Model 6



## Materials and finishes

Material	aluminium
Colour	Pure orange - 014 - RAL 2004

## Logistic data

Product dimensions	H.3300 L.730 P.289
Net weight	17.540 Kg
Gross weight	20.680 Kg
Package dimensions 1	H.720 L.480 P.300
Package dimensions 1	H.3020 L.300 P.300

## Certifications and warranties

CE	Pour fiche Média
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	3 years