



FINLIN

Ceiling suspended



reddot winner 2023




277



609



657



1.0

LED PCB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 SDCM3 L80|50K 0.31kg

	CODE
2.5m	270184CH_
2.5m	270184B_
10m	270484B5

OPTIONAL

cover plate adapter for concrete housing

	CODE
	900194B0

LIGHT COLOUR	LUMEN CRI	CODE
2700K	430 >90	3
3000K	440 >90	5




2.0

LED PCB 8W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 SDCM3 L80|50K 0.34kg

	CODE
2.5m	270284CH_
2.5m	270284B_
10m	270584B5

LIGHT COLOUR	LUMEN CRI	CODE
2700K	655 >90	3
3000K	670 >90	5



3.0

LED PCB 9W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | opal PMMA diffuser

IP20 SDCM3 L80|50K 0.38kg

	CODE
2.5m	270384CH_
2.5m	270384B_
10m	270684B5

LIGHT COLOUR	LUMEN CRI	CODE
2700K	870 >90	3
3000K	890 >90	5