



WEVER & DUCRÉ
LIGHTING

FINLIN FLOOR 1.0

470184B3

Project

Type

Notes

Quantity

Date

GENERAL

Floor , Surface

Tilt max 10°

Rotation 360°

Black Matt

RAL 9005^a

IP20

Interior

Output: 1380 lm

LED

2700 K

CRI ≥ 90

3 SDCM

3 SDCM

OPTICAL

Opal

ELECTRICAL

dimmable

220 - 240 V

Total connected power 13.0 W

Class 3


PHYSICAL

Diameter 10 mm

Height 1801 mm

2.7 kg

^a Color may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

FINLIN FLOOR 1.0

470184B3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.