

## Find Me 1 Mono Point (Trim/No Trim)

09.3751.30 - White

Recessed adjustable luminaire for indoor application. Remote power supply 500 mA not included.




### Main specifications

<b>Number of heads</b>	1	<b>Mountings</b>	Ceiling recessed
<b>Power</b>	6W	<b>Environment</b>	Indoor
<b>CCT</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	344		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	14
<b>Beam angle C90-270 (°)</b>	14



Beam Angle: 14°			SPOT
h(m)	E(lx)	D(m)	
1	4642	0.24	
2	1160	0.48	
3	516	0.72	
4	290	0.95	
5	186	1.19	

Luminous flux luminaire  
344 lm (EXTREME CUT OFF)

### Electrical


<b>Voltage (V)</b>	12.00	<b>Emergency</b>	Without
<b>Lamp holder</b>	LED	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable 1- 10V, Electronic dimmable DALI		

### Physical


<b>Color</b>	White	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable	<b>Spot diameter (mm)</b>	35
<b>Recessed depth (mm)</b>	137		
<b>Weight (kg)</b>	0.23		
<b>Tilt (°)</b>	70		

### Note

Accessories included (honeycomb and screening crosspiece). Remote power supply to be installed in an accessible place.



### Certification / Marking



## Find Me 1 Mono Point (Trim/No Trim)



---

Constant Current Power Supply for LED. 15-20W  
60.8911



---

Constant Current Power Supply for LED. Dimmable DALI. 10-20W  
60.8847



---

Constant Current Power Supply for LED. 1-10V switch or push dimming. 13-20W  
60.9188



---

Constant Current Power Supply for LED. 6W-100/14W-240V  
60.8880



---

Continuous current power supply. Switch by trailing and leading edge dimming, mains dimming or push dimming. 32W  
60.8534