

white fixtures with white adapter
other fixtures with black adapter



PIRRO on track


1-Phase



93



205




2.0 SPOT

LED COB 11W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector
1-phase Global® track adapter

IP20 310° 32° SDCM2 L70|55K 0.36kg

CODE		
		173264E_
		173264K_
		173264B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	2x360 >90	3
3000K	2x380 >90	5




4.0 SPOT

LED COB 20W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PC lens and reflector
1-phase Global® track adapter

IP20 310° 32° SDCM2 L70|55K 0.58kg

CODE		
		173464E_
		173464K_
		173464B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	4x360 >90	3
3000K	4x380 >90	5




2.0 OPAL

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PMMA cover
1-phase Global® track adapter

IP20 310° SDCM3 L80|60K 0.33kg

CODE		
		173284E_
		173284K_
		173284B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	270 >90	3
3000K	290 >90	5



4.0 OPAL

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium | PMMA cover
1-phase Global® track adapter

IP20 310° SDCM3 L80|60K 0.54kg

CODE		
		173484E_
		173484K_
		173484B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	710 >90	3
3000K	740 >90	5