






REKTOR RECESSED LED GE

Rektor, the surface-mounted spotlight by Modular, will guide the way around your space. Rektor is a surprising fixture, as it is highly directional despite the super-sleek housing. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Rektor is very versatile in use, as it can also be mounted on the MP78 light line. Recently launched Rektor recessed is nothing more, but also nothing less, than a highly adjustable ceiling spotlight. Pure essence of lighting.

Art. Nr. 12822009

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 65 h 70	
Weight	0.74kg	
Min. Distance	0.1	
IP	IP20	
Glow Wire Test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
Power supply	350mA	500mA
	31Vf	33Vf
Connected load	11W	16.25W
Lumen	900lm	1234lm
Efficacy	82lm/W	76lm/W
UGR	22	23
Adjustability	h 360° v -90°/+90°	



This label is available in other languages:
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	12821032	12821132	12822032	12822132
white struc	12821009	12821109	12822009	12822109

REKTOR RECESSED LED GE

ACCESSORIES	
HUE-DEVICE	
70000615	HUE TAP SWITCH
70000614	HUE DIMMER SWITCH
70000847	HUE SENSOR
HUE-BRIDGE	
70000616	HUE BRIDGE EU
70000617	HUE BRIDGE UK
HUE-MODULE	
13190030	MODULAR CONNECTED 1-10V WHITE COMPONENT
CONBOX	
10490330	CONBOX 112X172X100X236
GYPKIT	
12291330	GYPKIT 170X112 - Ø65

