



BOXY L LED 92733 WDL B-MMAT

251 67 811 922 WDL B-MMAT

AVAILABLE IN



BLACK-BLACK 251 67 811 922 WDL B-B

BLACK-FLEMISH BRONZE 251 67 811 922 WDL B-FBR

BLACK-FLEMISH GOLD 251 67 811 922 WDL B-FG

BLACK-GOLD MATT 251 67 811 922 WDL B-MMAT

WHITE-WHITE 251 67 811 922 WDL W-W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.WIRELESS DIMMABLE CONTROL 48V-DC EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	WDL = wireless dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	601lm // 7W // 90lm/W

Requirements	
LED POWER SUPPLY 48V-DC	

Accessories	
BOXY HONEYCOMB	
BOXY SOFTENING LENS	
BOXY GLASS SBL	



BOXY L LED 92733 WDL B-MMAT

251 67 811 922 WDL B-MMAT

For detailed installation instructions, please consult the manual: [251_67_811_XXX_WDL_HAND.pdf](#)


BOXY L LED 92733 WDL B-MMAT

251 67 811 922 WDL B-MMAT

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

12




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

29



21012 0230 LED POWER SUPPLY 48V-DC / 100W

12



21012 0240 LED POWER SUPPLY 48V-DC / 200W

24

BOXY L LED 92733 WDL B-MMAT

251 67 811 922 WDL B-MMAT

Light altering devices



Ø40



Ø45

251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



Ø40



Ø45

251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W



Ø40



Ø45

251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W

Notes: