DELTALIGHT®

BOXY L LED 93033 WDL B-MMAT

251 67 811 932 WDL B-MMAT

AVAILABLE IN
BLACK-BLACK 251 67 811 932 WDL B-B
BLACK-FLEMISH BRONZE 251 67 811 932 WDL B-FBR
BLACK-FLEMISH GOLD 251 67 811 932 WDL B-FG
BLACK-GOLD MATT 251 67 811 932 WDL B-MMAT
WHITE-WHITE 251 67 811 932 WDL W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.WIRELESS DIMMABLE CONTROL 48V-DC EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	WDL = wireless dimmable
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	628lm // 7W // 94lm/W

Requirements

LED POWER SUPPLY 48V-DC

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

DELTALIGHT®

BOXY L LED 93033 WDL B-MMAT

251 67 811 932 WDL B-MMAT

For detailed installation instructions, please consult the manual: **251_67_811_XXX_WDL_HAND.pdf**

DELTALIGHT®

BOXY L LED 93033 WDL B-MMAT

251 67 811 932 WDL B-MMAT

FINISH YOUR SPECIFICATION

LED power supplies			#
	**300 89 48 100**	LED POWER SUPPLY 48V-DC / 100W DIN	12 ☐
	**300 89 48 240**	LED POWER SUPPLY 48V-DC / 240W DIN	29 ☐
	**21012 0230**	LED POWER SUPPLY 48V-DC / 100W	12 ☐
	**21012 0240**	LED POWER SUPPLY 48V-DC / 200W	24 ☐

DELTALIGHT®

BOXY L LED 93033 WDL B-MMAT

251 67 811 932 WDL B-MMAT

Light altering devices



251 70 03 01 B BOXY HONEYCOMB B ☐

251 70 03 01 W BOXY HONEYCOMB W ☐



251 70 03 04 B BOXY SOFTENING LENS B ☐

251 70 03 04 W BOXY SOFTENING LENS W ☐



251 70 03 05 B BOXY GLASS SBL B ☐

251 70 03 05 W BOXY GLASS SBL W ☐

Notes: