



TWEETER M ON 1 92750 WDL
418 51 811 923 WDL

[Weblink](#)



Available colors: BLACK-CHROMED (418 51 811 923 WDL B-C)
WHITE-WHITE (418 51 811 923 WDL W-W)

ADJUSTABLE 0° - 45° / 355°
INCL.1 x LED WHITE 10,4W / CRI>90 / 2700K / 1032lm
INCL.1 x REFLECTOR WFL-50°
INCL.WIRELESS DIMMABLE CONTROL 48V-DC
EXCL.LED POWER SUPPLY 48V-DC

LED Technics: Light source: 1032 lm // 10 W // 105 lm/W
Luminaire: 791 lm // 12 W // 66 lm/W

48V-DC

Class: III





Weight: 0.8 KG
Protection level: IP20
Minimum distance: n.a.

Requirements: LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual. [418 51 811 XXX WDL HAND.pdf](#)

TWEETER M ON 1 92750 WDL
418 51 811 923 WDL

Related references
LED POWER SUPPLIES

Weblink / Specs sheet  LED POWER SUPPLY 48V-DC / 100W DIN 300 89 48 100 110-240V / 50-60Hz	Weblink / Specs sheet  LED POWER SUPPLY 48V-DC / 150 W 300 89 48 150 220-240V / 50-60Hz	Weblink / Specs sheet  LED POWER SUPPLY 48V-DC / 240W DIN 300 89 48 240 100-240V / 50-60Hz	Weblink / Specs sheet  LED POWER SUPPLY 48V-DC / 90 W 300 89 48 90 110-240V / 50-60Hz
---	--	---	--

TWEETER M ON 1 92750 WDL
418 51 811 923 WDL

Related project picture of product family:

