



**TWEETER M ON 1 93033 WDL**

418 51 811 932 WDL

[Weblink](#)



Available colors: BLACK-CHROMED (418 51 811 932 WDL B-C)  
WHITE-WHITE (418 51 811 932 WDL W-W)

ADJUSTABLE 0° - 45° / 355°  
INCL. 1 x LED WHITE 10,4W / CRI>90 / 3000K / 1075lm  
INCL. 1 x REFLECTOR FL-33°  
INCL. WIRELESS DIMMABLE CONTROL 48V-DC  
EXCL. LED POWER SUPPLY 48V-DC

LED Technics: Light source: 1075 lm // 10 W // 110 lm/W  
Luminaire: 856 lm // 12 W // 72 lm/W

48V-DC

Class: III

Weight: 0.8 KG  
Protection level: IP20  
Minimum distance: n.a.





Requirements: LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual. [418\\_51\\_811\\_XXX\\_WDL\\_HAND.pdf](#)

**TWEETER M ON 1 93033 WDL**  
**418 51 811 932 WDL**

**Related references**

**LED POWER SUPPLIES**

<a href="#">Weblink / Specsheat</a>	<a href="#">Weblink / Specsheat</a>	<a href="#">Weblink / Specsheat</a>	<a href="#">Weblink / Specsheat</a>
 <p>LED POWER SUPPLY 48V-DC / 100W DIN 300 89 48 100 110-240V / 50-60Hz</p>	 <p>LED POWER SUPPLY 48V-DC / 150 W 300 89 48 150 220-240V / 50-60Hz</p>	 <p>LED POWER SUPPLY 48V-DC / 240W DIN 300 89 48 240 100-240V / 50-60Hz</p>	 <p>LED POWER SUPPLY 48V-DC / 90 W 300 89 48 90 110-240V / 50-60Hz</p>

TWEETER M ON 1 93033 WDL  
418 51 811 932 WDL

Related project picture of product family:

