





TWEETER M ON 1 93050 DIM8 W-W

418 51 811 933 ED8 W-W

AVAILABLE IN

BLACK-CHROMED 418 51 811 933 ED8 B-C

WHITE-WHITE 418 51 811 933 ED8 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-50° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	835lm // 10W // 84lm/W


For detailed installation instructions, please consult the manual: [418_51_811_XXX_HAND.pdf](#)

TWEETER M ON 1 93050 DIM8 W-W

418 51 811 933 ED8 W-W

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



300 90 004 ED8 WIRELESS CONTROL DIM8



Notes: