





## TWEETER M ON 1 93050 WDL B-C

418 51 811 933 WDL B-C

AVAILABLE IN

**BLACK-CHROMED** 418 51 811 933 WDL B-C

**WHITE-WHITE** 418 51 811 933 WDL W-W



 [View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted, Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.8
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-50° INCL.WIRELESS DIMMABLE CONTROL 48V-DC EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	WDL = wireless dimmable
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	835lm // 10W // 84lm/W

### Requirements

LED POWER SUPPLY 48V-DC (Remote)

For detailed installation instructions, please consult the manual: [418\\_51\\_811\\_XXX\\_WDL\\_HAND.pdf](#)


# TWEETER M ON 1 93050 WDL B-C

418 51 811 933 WDL B-C

## FINISH YOUR SPECIFICATION


### LED power supplies

#




**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

16

Notes: