



TWEETER M ON 1 93050 WDL
418 51 811 933 WDL

[Weblink](#)



Available colors: BLACK-CHROMED (418 51 811 933 WDL B-C)
 WHITE-WHITE (418 51 811 933 WDL W-W)

ADJUSTABLE 0° - 45° / 355°
 INCL. 1 x LED WHITE 10,4W / CRI>90 / 3000K / 1075lm
 INCL. 1 x REFLECTOR WFL-50°
 INCL. WIRELESS DIMMABLE CONTROL 48V-DC
 EXCL. LED POWER SUPPLY 48V-DC

LED Technics: Light source: 1075 lm // 10 W // 110 lm/W
 Luminaire: 824 lm // 12 W // 69 lm/W

48V-DC

Class: III





Weight: 0.8 KG
 Protection level: IP20
 Minimum distance: n.a.

Requirements: LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual. [418_51_811_XXX_WDL_HAND.pdf](#)

TWEETER M ON 1 93050 WDL
418 51 811 933 WDL

Related references
LED POWER SUPPLIES

<p style="text-align: center;">Weblink / Specsheat</p>  <p>55 100 90</p> <p>LED POWER SUPPLY 48V-DC / 100W DIN 300 89 48 100 110-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>240 49 60</p> <p>LED POWER SUPPLY 48V-DC / 150 W 300 89 48 150 220-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>63 114 125</p> <p>LED POWER SUPPLY 48V-DC / 240W DIN 300 89 48 240 100-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>314 40 63</p> <p>LED POWER SUPPLY 48V-DC / 90 W 300 89 48 90 110-240V / 50-60Hz</p>
---	---	--	---

TWEETER M ON 1 93050 WDL
418 51 811 933 WDL

Related project picture of product family:

