



TWEETER M ON 2 92750 WDL

418 51 812 923 WDL

[Weblink](#)



Available colors: BLACK-CHROMED (418 51 812 923 WDL B-C)
WHITE-WHITE (418 51 812 923 WDL W-W)

ADJUSTABLE 0° - 45° / 355°
INCL. 2 x LED WHITE 10,4W / CRI>90 / 2700K / 1032lm
INCL. 2 x REFLECTOR WFL-50°
INCL. WIRELESS DIMMABLE CONTROL 48V-DC
EXCL. LED POWER SUPPLY 48V-DC

LED Technics: Light source: 2064 lm // 20 W // 105 lm/W
Luminaire: 1582 lm // 24 W // 66 lm/W

48V-DC

Class: III

Weight: 1.3 KG
Protection level: IP20
Minimum distance: n.a.





Requirements: LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual. [418_51_812_XXX_HAND.pdf](#)

TWEETER M ON 2 92750 WDL
418 51 812 923 WDL

Related references

LED POWER SUPPLIES

<p style="text-align: center;">Weblink / Specsheat</p>  <p>55 100 90</p> <p>LED POWER SUPPLY 48V-DC / 100W DIN 300 89 48 100 110-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>240 49 60</p> <p>LED POWER SUPPLY 48V-DC / 150 W 300 89 48 150 220-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>63 114 125</p> <p>LED POWER SUPPLY 48V-DC / 240W DIN 300 89 48 240 100-240V / 50-60Hz</p>	<p style="text-align: center;">Weblink / Specsheat</p>  <p>314 40 63</p> <p>LED POWER SUPPLY 48V-DC / 90 W 300 89 48 90 110-240V / 50-60Hz</p>
---	---	--	---

TWEETER M ON 2 92750 WDL
418 51 812 923 WDL

Related project picture of product family:

