





## TWEETER M ON 2 93033 DIM8 B-C

418 51 812 932 ED8 B-C

AVAILABLE IN

**BLACK-CHROMED** 418 51 812 932 ED8 B-C

**WHITE-WHITE** 418 51 812 932 ED8 W-W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted, Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.3
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY INCLUDED</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	2178lm // 17,2W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1735lm // 20W // 88lm/W

For detailed installation instructions, please consult the manual: [418\\_51\\_812\\_XXX\\_HAND.pdf](#)


## TWEETER M ON 2 93033 DIM8 B-C

418 51 812 932 ED8 B-C

### FINISH YOUR SPECIFICATION

#### Control gear, ballast and transformers

---



**300 90 004 ED8** WIRELESS CONTROL DIM8



Notes: