



**TWEETER M ON 2 93033 WDL**

418 51 812 932 WDL

[Weblink](#)



Available colors: BLACK-CHROMED (418 51 812 932 WDL B-C)  
WHITE-WHITE (418 51 812 932 WDL W-W)

ADJUSTABLE 0° - 45° / 355°  
INCL. 2 x LED WHITE 10,4W / CRI>90 / 3000K / 1075lm  
INCL. 2 x REFLECTOR FL-33°  
INCL. WIRELESS DIMMABLE CONTROL 48V-DC  
EXCL. LED POWER SUPPLY 48V-DC

LED Technics: Light source: 2150 lm // 20 W // 110 lm/W  
Luminaire: 1712 lm // 24 W // 72 lm/W

48V-DC

Class: III





Weight: 1.3 KG  
Protection level: IP20  
Minimum distance: n.a.

Requirements: LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual. [418\\_51\\_812\\_XXX\\_HAND.pdf](#)

**TWEETER M ON 2 93033 WDL**  
**418 51 812 932 WDL**

**Related references**  
**LED POWER SUPPLIES**

<p style="text-align: center;"><a href="#">Weblink / Specsheat</a></p>  <p>55 100 90</p> <p>LED POWER SUPPLY 48V-DC / 100W          DIN          300 89 48 100          110-240V / 50-60Hz</p>	<p style="text-align: center;"><a href="#">Weblink / Specsheat</a></p>  <p>240 49 60</p> <p>LED POWER SUPPLY 48V-DC / 150 W          300 89 48 150          220-240V / 50-60Hz</p>	<p style="text-align: center;"><a href="#">Weblink / Specsheat</a></p>  <p>63 114 125</p> <p>LED POWER SUPPLY 48V-DC / 240W          DIN          300 89 48 240          100-240V / 50-60Hz</p>	<p style="text-align: center;"><a href="#">Weblink / Specsheat</a></p>  <p>314 40 63</p> <p>LED POWER SUPPLY 48V-DC / 90 W          300 89 48 90          110-240V / 50-60Hz</p>
---	---	--	---

TWEETER M ON 2 93033 WDL  
418 51 812 932 WDL

Related project picture of product family:

