





TWEETER M ON 2 93050 WDL W-W

418 51 812 933 WDL W-W

AVAILABLE IN

BLACK-CHROMED 418 51 812 933 WDL B-C

WHITE-WHITE 418 51 812 933 WDL W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR WFL-50° INCL. WIRELESS DIMMABLE CONTROL 48V-DC EXCL. LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	WDL = wireless dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	1669lm // 20W // 84lm/W

Requirements

LED POWER SUPPLY 48V-DC (Remote)

For detailed installation instructions, please consult the manual: [418_51_812_XXX_WDL_HAND.pdf](#)


TWEETER M ON 2 93050 WDL W-W

418 51 812 933 WDL W-W

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

10



21012 0230 LED POWER SUPPLY 48V-DC / 100W

4



21012 0240 LED POWER SUPPLY 48V-DC / 200W

8

Notes: