
RJH-TS 2000W/230/C/R7S



Product Datasheet Date: 01.02.2023

















G

44000

2900K 2 000h

Dimmable

General Data

Article No.	22300605
Afficie No.	22300003
Code	RJH-TS 2000W/230/C/R7S
Product EAN	4008597006050
Customs tariff no.	85392192
Box quantitiy (pcs.)	12
EAN Box	4008597416057
Gross weight of box in kg	0.9
Length of box in m	0.12
Width of box in m	0.09
Height of box in m	0.4
ETIM class	EC000038
ETIM class name	High voltage halogen lamp
Weight	30 g
Product status	Inactive

Electric Parameters

Rated wattage	2000.0 W	
Lamp nominal wattage	2 kW	

RJH-TS 2000W/230/C/R7S



Electric Parameters

Power factor	1.00
Lamp voltage	230-230 V
Mains voltage	230 V
Lamp's nominal current	8.7 A
dimmable	Yes

Light Application Parameters

Luminous flux	44000 lm
Rated lamp luminous flux	44000 lm
Luminous efficiency	22 lm/W
Colour temperature	2900 K
Color rendering index Ra	100

Service Life

Average nominal lifespan	2000 h
No. switching cycles	50000

Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energy Label A to G	G
Energylabel A++ to E	С
Diameter	12 mm
Total length	327.4 mm
Contact distance I	327.4 mm
Burning position	p15
Mercury content	0.0 mg
Lamp shape	Tube, double-ended
Model	Clear
Base	R7s

Notes on Operation

Burning position	p15	

Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	HL
Directional or non-directional light	NDLS

RJH-TS 2000W/230/C/R7S



Type of color temperature

SINGLE_VALUE

RJH-TS 2000W/230/C/R7S



Miscellaneous

EU Directive DIM1

Notes

Mains voltage halogen lamp clear, tubular shape, 230V, double ended, base R7s, dimmable steplessly, 2000 h mean service life

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base




R7s IEC/EN 60061-1 sheet 7004-92A-4

Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in effiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps

400 500 600 700 nm

daylight(D 65)

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

RJH-TS 2000W/230/C/R7S



All technical data without guarantee.