



SCAR-LITE - 350mA

Material

frame : aluminium
flex : aluminium+metal - silicone
lens : PMMA

Materiaal

frame : aluminium
flex : aluminium+metaal - silicone
lens : PMMA

Matériau

structure : aluminium
flex : aluminium+métal - silicone
lentille : PMMA



Finish

black - white
flex : white or black silicone

Afwerking

zwart - wit
flex : witte of zwarte silicone

Finition

blanc - noir
flex : silicone blanc ou noir

Lightsource

1 x LED 0.96W (included)
warm white : 2700K - 114lm - CRI >93
beam : 42°

Lichtbron

1 x LED 0.96W (inclusief)
warm wit : 2700K - 114lm - CRI >93
lichtbundel : 42°

Source lumineuse

1 x LED 0.96W (inclus)
blanc chaud : 2700K - 114lm - CRI >93
rayon de lumière : 42°

Connection

110V- 230V - driver & switch included
(in base, non-dimmable)

Aansluiting

110V- 230V - voeding en schakelaar inclusief
(in base, niet dimbaar)

Connexion

110V- 230V - convertisseur et Interrupteur inclus
(encastré, non-dimmable)

Specifications

indoor
wall or ceiling mounting
class I
IP40

Specificaties

binnen
wand- of plafondmontage
klasse I
IP40

Spécifications

intérieur
applique ou plafonnier
classe I
IP40