

slat



slat one



slat + slat one Design: Klaus Nolting

slat + slat one Design: Klaus Nolting

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

dimmbar

Installation:
slat: 2 x Kabeleinführung;
slat one: 1 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas satiniert

Schutzart:
IP65

Lichtrichtung:


light technology:
230V Power LED
2700K + 3000K
L70/50.000 h














dimmable

installation:
slat: 2 x cable entry point;
slat one: 1 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass satined

protection class:
IP65

light direction:


	Farbe colour	2700K Art.-Nr. item no.	 Systemleistung system perform.	3000K Art.-Nr. item no.	Systemleistung system perform.
slat 	 anthracite RAL 7016	91130-27-AN	16 W/675 lm	91130-AN	16 W/685 lm
	 cool brown	91130-27-CB	16 W/675 lm	91130-CB	16 W/685 lm
	 space grey	91130-27-SG	16 W/675 lm	91130-SG	16 W/685 lm
	 pure white RAL 9016	91130-27-WH	16 W/675 lm	91130-WH	16 W/685 lm
	 deep black RAL 9005	91130-27-BL	16 W/675 lm	91130-BL	16 W/685 lm
slat one 	 anthracite RAL 7016	91131-27-AN	8 W/280 lm	91131-AN	8 W/294 lm
	 cool brown	91131-27-CB	8 W/280 lm	91131-CB	8 W/294 lm
	 space grey	91131-27-SG	8 W/280 lm	91131-SG	8 W/294 lm
	 pure white RAL 9016	91131-27-WH	8 W/280 lm	91131-WH	8 W/294 lm
	 deep black RAL 9005	91131-27-BL	8 W/280 lm	91131-BL	8 W/294 lm
Größe in mm size in mm					