# **FLOS**

#### **CAMOUFLAGE 240 MM**

Light distribution Symmetric Symmetric Class I Beam angle 151°

**Mounting** Wall surface

**Lamps description** Mid-Power Led: 12W - 1488 lm ≠ FIXT 898 lm - 3000K/CRI 80 - 220-240V

1. d. . . O . d. .

**Environment** Indoor, Outdoor

**Notes**We recommend using a connection system with a degree of

protection greater than or equal to the degree of protection

of the luminaire.

**Technical description**Dissipating aluminum body with diffuser in transparent polycarbonate. The Crema d'Orcia and Basaltina stone finishes

are made by fastening high-strength, high-resistance adhesive to a stone plate created by means of mechanical machining from a solid block. The concrete finishing is made by fastening a poured cement plate reinforced with fiberglass using a single component high strength, high-resistance adhesive. The Primer version is painted after installation with normal water-based colors (tempera, stucco, water-based paints) to ensure maximum uniformity with the architecture. The aluminum versions are finished with a high-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Upon commercial and technical evaluation, it is possible to create customized versions with other materials on request.

### **ELECTRICAL**

Transformer type Electronic
Transformer availability Included
Transformer mounting Integral
Emergency Without
Voltage (V) 220/240

### **PHYSICAL**

Aiming Fixed
Diameter (mm) 240
Weight (kg) max 1,50
Number of heads I




### Camouflage 240 mm

designed by Piero Lissoni

Collection of products for outdoor use, for wall installation with LED light source. Integrated 220/240V power source. Supplied with a 1000 mm section of outgoing neoprene cable. Version 110V upon request.

F1316000	Primer
F1316001	White
F1316006	Grey
F1316018	Deep Brown
F1316030	Black
F1316033	Anthracite
F1316087	Basaltina Stone
F1316089	Concrete
F1316090	Crema d'Orcia Stone

## **DIMENSIONS**



\*Concrete, crema d'orcia, basaltina H = 48 mm

# CERTIFICATIONS









# **FLOS**



# Camouflage 240 mm . Lamps



### Mid-Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## Camouflage 240 mm

designed by Piero Lissoni

Collection of products for outdoor use, for wall installation with LED light source. Integrated 220/240V power source. Supplied with a 1000 mm section of outgoing neoprene cable. Version 110V upon request.



# **DIMENSIONS**



\*Concrete, crema d'orcia, basaltina H = 48 mm

### **CERTIFICATIONS**









