



pip Design: Klaus Nolting

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

dimmbar

Installation:
1 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas satiniert

Schutzart:
IP65

Lichttrichtung:



light technology:
230V Power LED
2700K + 3000K
L70/50.000 h


dimmbare

installation:
1 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass satined

protection class:
IP65

light direction:



Farbe colour	2700K warm white		3000K	
	Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
 anthracite RAL 7016	91120-27-AN	6 W/273 lm	91120-AN	6 W/320 lm
 cool brown	91120-27-CB	6 W/273 lm	91120-CB	6 W/320 lm
 space grey	91120-27-SG	6 W/273 lm	91120-SG	6 W/320 lm
 pure white RAL 9016	91120-27-WH	6 W/273 lm	91120-WH	6 W/320 lm
 deep black RAL 9005	91120-27-BL	6 W/273 lm	91120-BL	6 W/320 lm

Größe in mm
size in mm