

# TUBE

Design by Ichiro Iwasaki.

## Reference

**6100.**

## Application

Ceiling Lamps

## Installation type

Surface

## Description

Ceiling lamp defined by its curved sheet aluminium shade lending a visual and material lightweight quality.

## Diffuser

Polycarbonate diffuser

## Materials

LED support: Aluminum

Ceiling rose: Steel

## Finish



**6100-10** White (NCS S 0300-N)



**6100-15** Grey L2 (NCS S 2500-N)




**6100-16** Grey M1 (NCS S 4500-N)



**6100-21** Grey D1 (NCS S 7000-N)

## Sketch



## Electrical characteristics

1 x LED PLATE 13,5W 700mA

Total 13.5 W



A+



**Light source:** 2700K CRI >90 1740 lm 128.8 lm/W

**Fixture:** 632 lm 46.81 lm/W

**Driver included:** CC - Constant Current 700 mA 110-240V 50/60Hz

**Electronic dimming** DALI 1-10V Push

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0402 m<sup>3</sup> /

Gross weight 3.0 kg. / Net weight 1.4 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

## Certificates

