



09.3812.CZA Bronze

### Find Me 1

Designed by Jorge Herrera, 2018



LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



# Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Lamp category	LED
Ilcos	No
Bulb finish	Clear
Number of heads	1
Power (W)	5.5
System power (W)	5.5
Source flux (lm)	450
System flux (lm)	309
Efficacy (lm/W)	56.18

# Physical

Colour	Bronze
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	33
Length (mm)	33
Net weight (kg)	0.11
IP internal	20
IP external	20

### Download

Mounting instructions



### Photometric Files

LDT / IES



# **Technical Drawings**

2D	<b>⊥</b> ZIP
3D	<b>⊥</b> ZIP
<b>⊕</b> Bim	<b>⊥</b> ZIP




















https://professional.flos.com/en/global/product/find-me-1-09.3812.cza/

09.3812.CZA

# Schematic light drawing



Bea	Beam Angle:	
h(m	) E(l×)	D(m
1	4168	0.2
2	1042	0.4
3	463	0.7
4	261	0.9
5	167	1.1

Beam Angle:		14'
h(m)	E(lx)	D(m
1	4168	0.24
2	1042	0.48
3	463	0.72
4	261	0.95

# **Ecodesign and Energy** Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGR <sub>L</sub>	4

#### Electrical

Insulation class	III
Main voltage (Vac)	24
LED voltage Vf (Vdc)	24.00
LED current (mA)	400
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1

#### **Notes**

Accessories included (honeycomb and screening crosspiece).