

Date

Name

Client

Project name

Quote#

Type/Quantity



04/09/2021 15:23:03

Specification Sheet

LOGIC MINI W S

304 31 12

[Weblink](#)



Opening formaat:  55 mm

Inbouwdiepte: 50 mm

Dikte montageoppervlak: min. 12

Beschikbare kleuren: ALU GRIJS (304 31 12 A)
WIT (304 31 12 W)

1 x LED 0,6W / 3000K / 40lm
EXCL. LED POWER SUPPLY 24V-DC
Not Dimmable

LED Technics: Lichtbron: 45 lm // 67 lm/W
Luminaire: 4 lm // 1 W // 2 lm/W

24V-DC

Klasse: III

Gewicht: 0.2 KG

Protection level: IP54

Minimumafstand: n.v.t.

Energy Class: G

Opties: CONCRETE BOX 188

Benodigheden: LED POWER SUPPLY 24V-DC


Voor gedetailleerde installatie-instructies, raadpleeg de handleiding: [304_30_12_HAND.pdf](#)

LOGIC MINI W S
304 31 12

Related references


LED VOEDINGEN

[Weblink / Specificatieblad](#)



LED POWER SUPPLY 24V-DC / 150W
300 89 24 150
100-240V / 0/50-60Hz
Aantal toestellen: 225

[Weblink / Specificatieblad](#)




LED POWER SUPPLY 24V-DC / 24W
21012 0160
220-240V / 50-60Hz
Aantal toestellen: 36

Related references

BETON DOOS

[Weblink / Specificatieblad](#)



CONCRETE BOX 188
270 11 188

LOGIC MINI W S
304 31 12

Gerelateerde project foto van product familie:

