

ToLEDo Retro Ball


ToLEDo RT Ball V3 CL 470LM 827 E27 SL

0027248



Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment-friendly - no mercury and lower CO2 emissions



PRODUCT OVERVIEW

IPC Code	0027248
Product name	ToLEDo RT Ball V3 CL 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740424
E-number SE	8295066
Luminous flux (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288272481

DATA TABLE

General data

IPC Code	0027248
Product name	ToLEDo RT Ball V3 CL 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature rated (°C)	25

ToLEDo Retro Ball

ToLEDo RT Ball V3 CL 470LM 827 E27 SL

0027248

Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740424
E-number SE	8295066

Optical data

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	4.5
Equivalent watt (W)	40
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Mains voltage (V)	230-240V~
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Inrush Current (A)	2.6
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	38
Max. Luminaires per 16A C Breaker	62
Max. Luminaires per 20A C Breaker	77

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	78
Nominal Product Diameter (mm)	45
Weight (kg)	0.02

Packaging

Single packaging type	Carton
Product EAN number	5410288272481
Packaging single length / height (cm)	9.8
Packaging single width (cm)	4.8
Packaging single depth (cm)	4.8

ToLEDo Retro Ball

ToLEDo RT Ball V3 CL 470LM 827 E27 SL


0027248

DUN14 (inner)	25410288272485
Units per inner package	6
Packaging inner length / height (cm)	15.3
Packaging inner width (cm)	11.1
Packaging inner depth (cm)	10.6
DUN14 (outer)	15410288272488
Units per outer package	60
Packaging outer length / height (cm)	54.7
Packaging outer width (cm)	33.1
Packaging outer depth (cm)	14.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS



ToLEDo Retro Ball

ToLEDo RT Ball V3 CL 470LM 827 E27 SL

0027248

